

Black Light Chalk MSDS

Section 1 - IDENTIFICATION

Supplier

Wildfire, Inc.
2908 Oregon Ct. Ste G1
Torrance, California 90503

Emergency Contact Information

800-937-8065

Chemical name and synonyms

Black Light Chalk

Product Name

Black Light Group including Bright Yellow, Light Green, Light Pink, Light Violet, Light Magenta, Light Red, Light Purple, Light Blue, Light Yellow, Light Flesh, Light Chartreuse, Brilliant Yellow, Light Gold, Light Orange, White, Medium Blue

Section 2 - COMPONENTS

Ingredients

Gypsum (calcium sulfate) (CAS# 7778-18-9) – approximately –45 % by weight

ACGIH TLV = 10 mg total dust/m³

OSHA PEL = 15 mg total dust/m³

Calcium Carbonate (CAS# 471-34-1) - approximately - 15 % by weight

ACGIH TLV-TWA = 10 mg total dust/m³

OSHA PEL = 15 mg total dust/m³

Talc (hydrous magnesium silicate) (CAS# 14807-96-6) - approximately - 15 % by weight

ACGIH TLV-TWA = 2 mg /m³

OSHA PEL TWA = 20 mppcf

Pigment Dispersion (mixture)- approximately -15 % by weight

No exposure limits have been established for this product.

Kaolin Clay (hydrous aluminosilicate) (CAS# 1332-58-7) - approximately - 10 % by weight

ACGIH TLV = 0.025 mg /m³ respirable

Silica (Quartz) (CAS# 14808-60-7) - approximately – 0.5-2.5 % by weight

ACGIH TLV-TWA (2000) = 0.05 mg respirable quartz dust/m³

OSHA PEL (8-hour TWA) = (10 mg respirable dust/m³)/(percent silica + 2)

Trace Ingredients

Trace amounts of naturally occurring elements might be detected during chemical analysis. Trace constituents may include vegetable oil which is used as a lubricant in the process.

Section 3 - HAZARD IDENTIFICATION

Potential Health Effects

Effects Resulting from Eye Contact:

Exposure to airborne dust may cause immediate or delayed irritation or inflammation.

Effects Resulting from Skin Contact:

Direct contact may cause dryness, or may cause mild irritation if an allergic predisposition exists.

Effects Resulting from Inhalation:

Exposure to fine particles may cause irritation to the moist mucous membranes of the nose, throat, and upper respiratory system. It may also leave unpleasant deposits in the nose.

Effects Resulting from Ingestion:

Although small quantities of this product are not known to be harmful, ill effects are possible if larger quantities are consumed. Black Light chalk should not be eaten.

Medical conditions which may be aggravated by, inhalation or dermal exposure:

Pre-existing upper respiratory and lung diseases.

Section 4 - FIRST AIDEyes

In case of contact immediately flush eye with plenty of water. Remove contact lenses, if worn. If irritation persists, get medical attention.

Skin

In case of contact, wash skin with plenty of soap and water. Call a physician if irritation develops and persists.

Inhalation of Airborne Dust

Remove to fresh air. Seek medical help if coughing and other symptoms do not subside.

Ingestion

May result in obstruction and irritation if ingested, get medical attention.

Section 5 - FIRE AND EXPLOSION DATA

Flash point	None	Lower Explosive Limit.....	None
Upper Explosive Limit.....	None	Auto ignition temperature.....	Not Combustible
Extinguishing media.....	Not Combustible	Special fire fighting Procedures.....	None
Hazardous combustion products.....	None	Unusual fire and explosion hazards..	None

Section 6 - ACCIDENTAL RELEASE MEASURES

Collect dry material using a scoop. Avoid actions that cause dust to become airborne. Avoid inhalation of large quantities of dust and contact with skin.

Wear appropriate personal protective equipment as described in Section 8.

Small quantities can be disposed of with general refuse, contact your refuse hauler for more details.

Section 7 - HANDLING AND STORAGE

Keep product dry until used. Normal temperatures and pressures do not affect the material.

Section 8 - EXPOSURE CONTROLS/PERSONAL PROTECTIONRespiratory Protection

Avoid actions that cause large quantities of dust to become airborne. Use local or general exhaust ventilation to control exposures below applicable exposure limits.

Use NIOSH/MSHA approved dust masks or filtering face piece is recommended in poorly ventilated areas or when PEL may be exceeded.

Ventilation

Use local exhaust or general dilution ventilation to control exposure within applicable limits.

Eye Protection

Where potentially subject to splashes or puffs of dust, wear safety glasses with side shields or goggles.

Section 9 - PHYSICAL AND CHEMICAL, PROPERTIES

Appearance.....Solid	Odor.....No distinct odor
Physical state.....Solid (powder)	pH (in water).....N/A
Solubility in water...Slightly soluble	Vapor pressure.....N/A
Vapor density.....N/A	Boiling point.....N/A (i.e., > 1000 C)
Melting point.....N/A	Specific gravity (H2O = 1.0).....N/A
Evaporation rate.....N/A	

Section 10 - STABILITY AND REACTIVITYStability

Stable.

Reactivity

N/A

Section 11 - OTHER INFORMATION

SELLER MAKES NO WARRANTY, EXPRESSED OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY Wildfire Inc, except that the product shall conform to contracted specifications. The information provided herein was believed by Eternity Arts to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information to comply with all laws and procedures applicable to the safe handling and use of product and to determine the suitability of the product for its intended use. Buyer's exclusive remedy shall be for damages and no claim of any kind, whether as to product delivered or for non-delivery of product, and whether based on contract, breach of warranty, negligence, or otherwise shall be greater in amount than the purchase price of the quantity of product in respect of which damages are claimed. In no event shall Seller be liable for incidental or consequential damages, whether Buyer's claim is based on contract, breach of warranty, negligence or otherwise.