



Wildfire UltraBlade® LED Series


Dual Lamp LED Black Light Fixtures

UltraBlade Lighting from Wildfire is a unique linkable black lighting system that combines Wildfire's powerful SableLED® 365nm black light LED lamp technology in a series of slim profile fixtures with variety of wiring and mounting options.



Features:

- Advanced Self Ballasted UV LED Lamps
- Powerfull Twin Lamp Design
- Convenient Universal Voltage Input
- Flicker and RF Interference Free
- Positive Locking Sockets
- Optional Mounting Brackets
- Heavy Gauge Aluminum Housing
- Designed and Built in the USA



Standard Equipment:

- 106-052 | PowerCON Output Cable Connector
- 142-004 | Two 4' SableLED LED Lamps

Optional Accessories:

- 147-040 | Adjustable L Bracket Kit
- 147-041 | Floor Stand Kit
- 147-021 | Truss Clamp
- 147-002 | Safety Cable
- 147-003 | T-Bar Ceiling Mount

Ordering Example: (Select item from each box)

Model	Size	Lamps	Connections
UB	4	2	

Connections

- 1 - PowerCON
- 2 - Hard Wire

Specifications:

Housing:	18 Ga. aluminum with stainless steel hardware
Finish:	Flat black powder coat
Mounting:	Keyhole slot or optional adjustable brackets
Sockets:	Two positive locking medium Bi Pin G13
Input Voltage:	120 - 240VAC
Input Current:	.36A Max
Frequency:	50-60Hz.
Power Factor:	0.83
Power Consumption:	30W
Operating Temperature:	-4° to 113° F / -20° to 45° C
Humidity:	0-80% non condensing
Power Cord:	9' 16/3 SJT with PowerCON and NEMA 5-15-P (UB-42-1)
Power Input Connection:	Neutrik PowerCON (UB-42-1)
Power Output Connection:	Neutrik PowerCON, Max 4.0A (UB-42-1)
Lamps:	Two Wildfire SableLED® L15T8/BLB UV LED Lamps
Peak Wavelength:	365nm ± 10nm
Radiant Power:	1200 mW/m ² at .5m
Beam Angle:	160°
Lamp Life:	20,000 Hours
Weight:	4.40lbs / 1.99kg
IP Rating:	IP-20 Indoor Use
Warranty:	Three years parts & labor
Listing:	ETL 5004307

Features & Options:



PowerCON Connectors



Optional L Brackets



Optional Truss Clamps



Optional Floor Stands



Project	Approval / Date
Location	Fixture Type