



**WILDFIRE®
SHEEN LEVELER**

DESCRIPTION AND USES

Wildfire® Sheen Leveler was originally developed for the scenic studios of Hollywood to create dramatic visual effects for film, television and amusement parks. Wildfire brand paint and coating products have become the standard of quality for the visual effects professional. Designed to eliminate the visible variation in sheen between the painted image and the surrounding area, Wildfire Sheen Leveler is the Ideal protective top coating for all Wildfire Luminescent Clear Color Paints. Wildfire Sheen Leveler dries quickly to a smooth flat sheen that is water resistant and flexible.

For use over Invisible Clear Colors only. Images created with Invisible Clear Colors may still be detected in visible light due to variations in the sheen. For example, a stenciled image over a dead flat surface. To eliminate the visible variation in sheen, apply Sheen Leveler over the painted image and the surrounding area.

PRODUCTS

SKU	DESCRIPTION (32 Oz. 2 Pack)
WF30732	Wildfire Sheen Leveler

PRODUCT APPLICATION

SURFACE PREPARATION

Allow your project to dry for 24 to 48 hours before applying Sheen Leveler. Painted surface should be clean, dry and fully cured prior to application. Apply on a small test area to ensure desired effect is achieved.

Product is ready to use, do not dilute with water. For best results apply with an airbrush, HVLP spray equipment, artist brushes or varnish roller. Apply two coats of Sheen Leveler over the entire completed project for total invisibility. Do not apply when air and surface temperatures are below 50°F (10°C) or high humidity conditions exist. Optimal conditions are 60°F (16°C) to 80°F (27°C) and 30% to 60% relative humidity. Stir thoroughly before use.

NOTE: DO NOT SHAKE.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT INFORMATION

DRY TIME

Dry-to-touch is approximately 30 minutes, re-coat time is approximately 2 hours. Dry time will vary with temperature and humidity.

COVERAGE

Approximately 70 sq.ft/quart (6.5 M2/946 mL).

CLEAN UP

Clean tools, brushes, and equipment with warm, soapy water immediately after use. Promptly wipe up spills and splatters with a damp cloth.

HANDLING & STORAGE

Store out of direct sunlight. To avoid skinning, close container after each use. Keep lid tightly closed during storage.

NOTE: PROTECT FROM FREEZING.

Close tightly all containers when not in use. Store in a cool dry place away from direct sunlight. Do not freeze. If Wildfire Paints become frozen, allow the paint to completely thaw and come to room temperature before use. Stir thoroughly before use.

DISPOSAL

Dispose of unused or unwanted product in accordance with local laws regulating water-based coatings.

		TECHNICAL DATA	MDM-41
		WILDFIRE® SHEEN LEVELER	

PHYSICAL PROPERTIES

		WILDFIRE SHEEN LEVELER
Resin Type		Water, Water-Based Acrylic
Pigment Type		Fumed Silica
Solvents		Water, Glycol Ether
Weight	Per Gallon	8.68 lbs.
	Per Liter	1.04 kg
Solids	By Weight	21.16%
	By Volume	20.35%
Volatile Organic Compounds		92 g/l
Recommended Dry Film Thickness (DFT) per Coat		1 mil
Wet Film to Achieve DFT (Unthinned material)		4.9 mil
Practical Coverage at Recommended DFT (assume 15% material loss)		277 sq ft./gal.
Dry Times at 77°F (25°C) and 50% Relative Humidity	Touch	30 Minutes
	Handle	1 Hour
	Recoat	2 Hours
	Full Cure	12 Hours
Shelf Life		4 Years
Flash Point		>200°F (93°C)
Safety Information		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.